

# FieldShield®

## Riser Rated 10/6 mm Microduct



### Application

Simplifying the placement of fiber, while providing protection for all indoor elements, FieldShield Riser Rated 10/6 mm Microduct is specifically designed for applications requiring small pathways in confined spaces. Rugged crush resistance protects FieldShield Riser Rated 10/6 mm Microduct from the rigors of all industry standard deployment methods, while the rigid column strength allows microducts to be deployed through occupied duct previously thought to be exhausted. Riser Rated 10/6 mm Microduct has an outer diameter of 10 mm and an inner diameter of 6 mm.



### Description

FieldShield Riser Rated 10/6 mm Microduct is a durable, crush resistant micro-conduit designed to increase the protection of fiber while decreasing installation and maintenance expenses. Manufactured using high density thermoplastic, FieldShield Riser Rated Microduct offers superior durability and protection.

### Features and Benefits

#### Integrity

- Compliant to Telcordia GR-3155
- UL-2024 listed

#### Protection

- Quick and easy to install
- Riser Rated 10/6 mm Microduct has high tensile strength and crush resistance
- Designed for applications designated as riser air space

#### Access

- Industry standard beige provides high visibility for indoor installation applications in existing conduit and by itself
- Standard nylon pull string simplifies deployment of fiber
- Smooth core slip lining reduces drag co-efficient enabling fiber to be pushed or pulled with minimal resistance

#### Investment

- Maximizes capacity of existing conduit previously considered exhausted
- Provides industry leading protection for any indoor riser rated application

# FieldShield®

## Riser Rated 10/6 mm Microduct



### Technical Specifications

FieldShield Riser Rated 10/6 mm Microducts	
Length	2,000 feet (609.60 m) per spool (-0 / +5%)
Outside Diameter	0.394" (10.01 mm)
Inside Diameter	0.246" (6.25 mm)
Wall Thickness	0.074" (1.88 mm)
Slip Layer	Minimum 0.004" (0.102 mm)
Ovality	≤ 5%
Installation Tension	340 lbf
Minimum Bend-Radius	132.08 mm/5.2" radius
Material	Thermoplastic
Operating Temperature	-40°F to 176°F (-40°C to 80°C)
Installation Temperature	-14°F to 158°F (-26°C to 70°C)
Color	White
Markings	Part number, lot number, footage markers every two feet (609.60 mm)
Spool Size	12" ID x 24" OD x 14" W (304.80 mm x 609.60 mm x 355.60 mm)
Weight	84 lbs

### Pre-Configured Part Numbers

Part Number	Description
FS-DCR-NT-610-PS-2000F	FieldShield Microduct, 10 mm, riser, non-toneable, white, 2,000 foot (609.60 m) spool