

Application

The CraftSmart Fiber Outlet allows for easy demarcation inside the premise and cable management for incoming feeder cable.

Description

The CraftSmart Fiber Outlet can accommodate 4 entrance points for 3mm cable and up to 4 output of SC adapter ports. The splice cassette is hinged and easily removable for non-splicing applications. This small indoor enclosure provides both bend limiting protection and a secure termination point to connect the entrance fiber to the included equipment jumper.



Features and Benefits

Integrity

- Supports industry standard SC adapters

Protection

- Snap-on cover for duct free protection

Access

- Easy installation
- Accommodates 4 adapter ports
- Four cable entrance points

Investment

- Cables can be connected without splicing
- Hinged and detachable splice tray



Technical Specifications

CraftSmart Fiber Outlet	
Dimensions	3.9 x 3.2 x 1.25 inches (100 x 80 x 32 mm)
Color	White
Operating Temperature	-20°C to 60°C
Material	ABS
Adapter Style Receptacle	SC and LC
Adapter Slots	4 Slots
Accessories	Removable Storage Tray

Pre-Configured Part Numbers

Part Number	Description
021336	Fiber Outlet, 4 Ports, White
FS-FOB-SPLICEKIT-01	Fiber Outlet Box, SC/APC Prestripped Pigtail 2mm, SC/APC to SC/APC White FLEXdrop, 10 Foot, Splice Sleeve, SC/APC Adapter